

Nikon SB 29s



This speedlight lets you use TTL automatic exposure for shadowless wraparound macro photography. Two built-in flash modules provide full-surround illumination, so you can capture flawlessly the details of the world in miniature, without distracting shadows. This flexible unit lets you adjust the flash output to have either the right or left modules flash, or both together. Moreover, modelling flash mode lets you see through the viewfinder what effect the flash will have on your scene before you take the shot. A convenient focus illuminator ensures pinpoint focus adjustment, and a wide illumination panel lets you shoot flash-to-subject distances closer than 40mm.

www.dooyoo.co.uk :: Photography :: Photographic Flash :: Nikon SB 29s

General	
Width	13.3 cm
Depth	2.9 cm
Height	11.9 cm
Weight	410 g

Camera Flash	
Type	Ring-type flash
Guide Number (m / ISO 100)	11
Lens Coverage	20mm
Supported Exposure Control	TTL
Min Flash Duration	0.18 ms
Max Flash Duration	0.7 ms
Colour Temperature	Daylight
Manual Power Control Levels	1/1, 1/4, 1/32
Auto Shut-Off	Yes
Features	AF illuminator, modelling flash capability, Sync/multiple flash terminal

Power	
Power Consumption	Recycling time - 3 sec / 300 flash(es) - with 4 x AA type - Alkaline Recycling time - 2 sec / 170 flash(es) - with 4 x AA type - Nickel Metal Hydride Recycling time - 4 sec / 350 flash(es) - with 4 x AA type - lithium

Required Battery	4 x battery - AA type
------------------	-----------------------